

3005020011

## **CU-200**

Central Unit for CTB-20

---



---

### **DESCRIPTION**

- Central unit 20 lines for the CTB-100V system
- Operates with CTB-20 and CTB-20 W/V01 panel units
- AUX / Alarm input
- Output to Public Address system
- 24 VDC power supply
- 100V line output
- High power amplification by use of external 100V power amplifier

# SPECIFICATIONS

## GENERAL

Material / finish:	Aluminium / black
Mounting	Bulkhead with 4 x 4 mm screws
Terminals	Plugable screw terminals for cable max. 2.5 mm <sup>2</sup>
Fuses	F1, F2, F3, F4, 1 A 5 x 20
DIP-switches	For PA-zones, set priority, set receive call
Pot.meter	For volume setting line 1-5, 6-10
Dimension (mm)	400W x 400H x120D
Weight	Approx. 3.2 kg
External connections	4x Operation panels, up to 20 substations, AUX, PA
AUX input	0 dB 0,775 V/600 ohm
Alarm contact	Potential free N/O
Frequency range	200 Hz - 8 KHz (-3 dB)
Temperature operating	-20 to +55 °C
Power supply	20 - 32 VDC
Power consumption at 24 VDC	2.5 A
Output power	30 W per 10 lines
Output impedance	20 ohm per line
IP-rating	IP-22