
















































Connector versions and pin assignment

Level contact = L1 lowest contact

Temperature sensor mounted at the lowest position

serial No. Date

IN-GB- 001 08/18

| Connector versions | Level contact 01/03 | | Level contact 02/04 | | Level contact 01/03 + Pt100 - 3-wire connection |
|---|---|---|--|---|---|
| | Level contact L1 | Level contact L1-L3 + Thermal contact T | Level contact L1 | Level contact L1-L3 + Thermal contact T | Level contact L1 + Pt100 Three-wire connection |
|  <p>Plug socket connector 3+PE IP65 EN 175301-803 (DIN 43650)</p> |  |  |  |  |  |
|  <p>Plug socket connector 6+PE IP65 EN 175201-804 (DIN 43651)</p> |  |  |  |  |  |
|  <p>Plug socket connector 3 pol.+PE IP67</p> |  |  |  |  |  |
|  <p>Plug socket connector 6 pol.+PE IP67</p> |  |  |  |  |  |
|  <p>Plug socket connector HAN I IP65</p> |  |  |  |  |  |
|  <p>Plug socket connector HAN II IP65</p> |  |  |  |  |  |
| Steckervarianten | Level contact 01/03 | Level contact 02/04 | Level contact 01/03 + Pt100 - 3-wire connection | | |
|  <p>Plug socket connector Serie M12 IP67 Recommended value when used outside enclosed buildings or in damp locations</p> |  |  |  |  |  |
| |  |  |  |  |  |

