

## PNOZ s30 24-240VACDC 2 n/o 2 n/c

750330



PNOZsigma Safety relay (standalone). Outputs: 2 N/O, 2 N/C, UB 24 - 240 V AC/DC, width: 45 mm  
 Speed-, standstill monitor of the PNOZsigma product group, proximity switch and/or incremental encoder, display operation Push & Turn, Plug-in terminals of screw type, expansion with PNOZsigma Contact expansion.

On request

1 PC Available ex-stock  
 Availability

### Technical details

Certifications:	CE, cULus Listed, EAC (Eurasian), TÜV, CCC
Application options:	Speed monitoring, Standstill monitoring
Operating modes:	Single-channel, Automatic reset, Dual-channel, Manual reset, Monitored manual reset
Standards:	EN 1088, EN 60204-1, EN 62061, EN ISO 10218-1, EN ISO 13849-1, VDI 2854
Supply voltage (V):	24,0 - 240,0
Supply voltage type:	AC/DC
Terminal type:	Screw terminal
Max. current at DC13 I (6 cycles/min):	4.0 A
Width dimension:	45.0 mm
Height dimension:	98.0 mm
Depth dimension:	120.0 mm
Gross weight:	425 g
Net weight:	405 g
Ambient temperature:	-20 - 55 °C

### Related Products

Top 

Webcode: 7992